PL988



PROPERTY	DESCRIPTION		
Primary/Stalk Yarn Type:	Polyethylene		
Secondary/Thatch Yarn Type:	N/A		
Yarn Cross Section:	Texturized Polyethylene		
Standard Color(s)*:	Field		
UV Stabilized:	Yes		
Fabric Construction:	Tufted		
Primary Backing:	ArmorLoc [™] 3L Stabilized Woven PP/PET Multilayer		
Coating Type(s):	5mm Polyurethane Foam		
Perforations:	Not Recommended		
Yarn Denier/Ends:	5600/8		
Pile Height:	3/4"		
Face Weight:	48 oz/yd²		
Fabric Width:	15 ft.		



APPLICATION

PL988 is a multipurpose turf solution designed to withstand high-traffic use. Its short-pile, texturized polyethylene construction is engineered for long-lasting, low-maintenance performance. The 5mm polyurethane foam backing provides added cushioning when installed over concrete or a compacted aggregate base, and this turf is suitable for both indoor and outdoor use.









PL988

FINISHED FABRIC Nominal Specification	ENGLIS	ENGLISH SYSTEM		SYSTEM	ASTM TEST
	Value	Units	Value	Units	Method
Pile Height (Nominal)	.75	ln.	19	mm.	D-5823
Face Weight	48	oz/yd²	1,627	g/m²	D-5848
Total Fabric Weight	133	oz/yd²	4,509	g/m²	D-5848
Primary Backing Weight	7	oz/yd²	237	g/m²	D-5848
Secondary Coating Weight	78	oz/yd²	2,645	g/m²	D-5848
Tuft Bind	>10	lbs.	>4.5	Kg.	D-1335
Grab Tear Strength (Average)	>200	lbs.	>91	Kg.	D-5034
Lead Content	<50	ppm	<50	ppm	F-2765
Total Yarn Linear Density	5,600	Denier	6,216	D-Tex	D-1577
Tensile Strength	8	lbs.	3.6	Kg.	D-5034
Machine Gauge	0.1875	ln.	0.5	Cm.	D-5793
Flammability	TEST	PASSED	TEST	PASSED	D-2859
Fiber Thickness	-	_	100	microns	None



